



TATA INTERNATIONAL KENYA

INTRA V20



Walk-through Cabin



Best-in-class Gradeability



Gear Shift Advisor (first time in SCVs)



Bigger tyres for better load carrying capability



Lower NVH levels in the SCV range



EQUIPMENT SALES KENYA LTD

"Your Quality Equipment Partner"

+254 728 355530



+254 712 646360



www.eskl.co.ke



sales@eskl.co.ke



P.O. BOX 31853-00600
Nairobi.



Thika Rd, Exit 10 Next to Kenya Clay



INTRA V20



TECHNICAL SPECIFICATIONS

ENGINE

ENGINE CAPACITY

1396 cc

ENGINE POWER

70 HP @ 4000 RPM

MAX. TORQUE

140 Nm @ 1800-3000 RPM

MAX. SPEED

80 Kmph

MAX. GRADEABILITY AT RATED GVW

45%

DRIVELINE

GEARBOX

Manual, 5-Forward 1-Reverse

CLUTCH

Single plate dry friction diaphragm type

STEERING AND BRAKES

STEERING

Power Steering

FRONT BRAKES

Disc brakes

REAR BRAKES

Drum brakes

SUSPENSION

FRONT SUSPENSION

Semi-elliptical leaf spring

REAR SUSPENSION

Semi-elliptical leaf spring

DIMENSIONS

WHEELBASE

2250 mm

OVERALL LENGTH

4282 mm

OVERALL WIDTH

1639 mm

OVERALL HEIGHT

1918 mm

GROUND CLEARANCE

170 mm

LOAD BODY

Pickup type, Hinged rear tailgate

LXWXH (IN M)

2.45 X 1.54 X 0.40

TURNING RADIUS

4750 mm

WEIGHT

GVW

2300 Kg

KERB WEIGHT

1200 Kg

TYRE

165 R14 LT 8PR (Tubeless)

FUEL TANK

35L

VENTILATION

HVAC

+254 728 355530



+254 712 646360



www.eskl.co.ke



P.O. BOX 31853-00600
Nairobi.



sales@eskl.co.ke



Thika Rd, Exit 10 Next
to Kenya Clay