



TATA INTERNATIONAL KENYA

INTRODUCING

**XENON
YODHA**



**BEST
IN
CLASS**

GRADEABILITY
GROUND CLEARANCE
POWER & TORQUE



EQUIPMENT SALES KENYA LTD

"Your Quality Equipment Partner"

+254 728 355530



+254 712 646360



www.eskl.co.ke



sales@eskl.co.ke



P.O. BOX 31853-00600
Nairobi.



Thika Rd, Exit 10 Next
to Kenya Clay



STRONG AGGREGATES

ENGINE The newly redesigned TATA 4 SPCR TCIC 4-CYLINDER 3.0 L engine with a capacity of 2956 cc is powered to perform.

POWER 86 HP power with 250 Nm Torque.

SPEED Unrivalled Speed.

LARGEST LOAD BODY Rated payload of 1500 kgs.

HIGHEST GROUND CLEARANCE With ground clearance of 210mm, its the highest in the category.

TYRES The wide 16 (215/75 R) radial tyres of the Yodha ensure better safety.

SUSPENSION
Front: 6 Semi-Elliptical Leaf Springs + Anti-Roll bar
Rear: Innovative Two-stage Semi-Elliptical Leaf Springs 9 Leaves.

SOPHISTICATED COMFORT

FLAT BENCH SEAT Accommodates 3 people comfortably, unlike any in the category.

LOCKABLE GLOVE BOX Keep your important documents safe.

TRIP METER WITH DUAL READING A unique feature that is ideal for Fleet Owners to keep track of the vehicle movement & routes taken during the journey.

INTENSITY CONTROL CABIN LIGHT Allows the driver to adjust the intensity of the cabin light, depending upon the surroundings outside.

ADJUSTABLE ANTI-GLARE REAR VIEW MIRROR The rear view mirror of the Yodha can be adjusted by the driver to reduce the glare from outside.

WORLD-CLASS CABIN SPACE Newly designed spaces for maximum comfort.

FLUID PERFORMANCE

SUPER GRADEABILITY OF 30% Allows you to climb up the steep slopes of the valley and mountains with ease.

GREAT RESTART GRADEABILITY OF 22% Keep climbing them even after sudden stops on steep roads.

FASTER PICK-UP Enables faster trips.

EFFECTIVE BRAKING Ensures complete safety while driving.

FEATURES

YODHA BS IV

ENGINE

Type Tata 4SPCR TCIC 4-cylinder BS IV
Capacity 2956 cc
Max. Output 64 kW (85 HP) @ 3000 rpm
Max. Torque 250 Nm@ 1000-2000 rpm
Fuel Tank Capacity 45 L

CLUTCH & TRANSMISSION

Clutch Single plate dry friction type 260 mm Dia
Gearbox GBS 76 5/4.1
Steering Synchronesh 5 forward + 1 reverse
Power steering

SUSPENSION

Front 6 Semi-Elliptical Leaf Springs
Rear Innovative two-stage Semi-Elliptical Leaf Springs - 9 Leaves
Anti-roll bar Front

BRAKES

Front Hydraulic, twin-pot Disc Brakes
Rear Drum Brakes

WHEELS & TYRES

Tyre 215/75 R 16 Radial
Rim size 16-Inch

OVERALL VEHICLE DIMENSIONS (mm)

Width 1860
Length 5350
Height 1810
Ground Clearance 210
Wheel Base 3150
Internal Load Body (L x B) 2550 (8.4 ft) x 1750 (5.7 ft)
Turning Circle Radius 6250

WEIGHT (kg)

Payload 1500 kgs.

PERFORMANCE

Gradeability 30%
Restart Gradeability 22%
Top Speed
Seating type Lay Flat Seat

+254 728 355530



www.eskl.co.ke



sales@eskl.co.ke



+254 712 646360



P.O. BOX 31853-00600
Nairobi.



Thika Rd, Exit 10 Next
to Kenya Clay